Attorney Docket 10420/12

VIII. Appendix, Claims in the Application

- 1. (Original) An aircraft skin lap router apparatus, comprising:
- a guide, fastened to the skin by fasteners drilled through the skin;
- a platform, mounted on the guide:
- a router having a vertical adjustment, mounted on the platform; and
- a vacuum fitting, mounted on the platform, wherein an operator adjusts the router vertical adjustment for a desired depth-of-cut on the aircraft skin lap, the router cuts the skin lap, and removes debris via the vacuum fitting.
- 2. (Original) The apparatus of Claim 1, wherein a vertical height setting may be made within one-thousandth of an inch using the router vertical adjustment.
- 3. (Original) The apparatus of Claim 1, wherein the router is selected from the group consisting of a pneumatic router and an electric router.
- (Original) The apparatus of Claim 1, wherein the router has a speed adjustment.
- 5. (Original) The apparatus of Claim 1, further comprising an end mill attached with the router.
- 6. (Original) The apparatus of Claim 5, wherein the end mill is a 0.250", three-fluted end mill.
 - 7. (Original) The apparatus of Claim 1, further comprising grips on the router.

Attorney Docket 10420/12

- 8. (Original) The apparatus of Claim 1, wherein the guide is a plastic material and is formed to a uniform height and width.
 - 9. (Original) The apparatus of Claim 8, wherein the guide is a nylon profile.
- 10. (Original) The apparatus of Claim 1, further comprising at least one bearing mounted on the platform and interfacing with the guide.
- 11. (Original) The apparatus of Claim 3, further comprising air fittings attached to the platform for receiving air from an air supply and for delivering air to a pneumatic router.
 - 12. (Original) A sheet metal router apparatus, comprising:
- a guide, fastened to the sheet metal by fasteners drilled through the sheet metal;
 - a platform, mounted on the guide; and
- a router having a vertical adjustment, mounted on the platform, wherein an operator adjusts the router vertical adjustment for a desired depth-of-cut and moves the platform continuously along the guide to make a desired cut.
- 13. (Original) The apparatus of Claim 12, wherein a vertical height setting may be made within one-thousandth of an inch using the router vertical adjustment.
- (Original) The apparatus of Claim 12, further comprising a vacuum fitting mounted on the platform.
- 15. (Original) The apparatus of Claim 12, wherein the router is selected from the group consisting of a pneumatic router and an electric router.

Attorney Docket 10420/12

- 16. (Original) The apparatus of Claim 12, wherein the router has a speed adjustment.
- 17. (Original) The apparatus of Claim 12, further comprising an end mill attached with the router.
- 18. (Original) The apparatus of Claim 17, wherein the end mill is a 0.25", three-fluted end mill.
- 19. (Original) The apparatus of Claim 12, wherein the guide is a plastic material formed to a uniform height and width.
- 20. (Original) The apparatus of Claim 12, further comprising at least one bearing mounted on the platform and interfacing with the guide.
- 21. (Original) The apparatus of Claim 15, further comprising air fittings attached to the platform for receiving air from an air supply and for delivering air to a pneumatic router.
 - 22. (Original) An aircraft skin lap router apparatus, comprising:
 - a nylon guide, fastened to the skin by fasteners drilled through the skin;
- a platform, mounted on the guide, the platform interfacing with the guide through at least one bearing;

a router having a vertical adjustment within one-thousandth of an inch, mounted on the platform, said router having at least two hand grips and a speed adjustment, and adapted to receive a source of power;

an end mill mounted removably on the router; and

Attorney Docket 10420/12

- a vacuum fitting, mounted on the platform, wherein an operator adjusts the router vertical adjustment for a desired depth-of-cut on the aircraft skin lap, the router cuts the skin lap, and removes debris via the vacuum fitting.
- 23. (Original) The router apparatus of Claim 22, wherein the source of power is electric or pneumatic.
 - 24. (Original) A sheet metal router apparatus, comprising:
- a nylon guide, fastened to the sheetmetal by fasteners drilled through the sheetmetal;
- a platform, mounted on the guide, the platform interfacing with the guide through at least one bearing;
- a router having a vertical adjustment within one-thousandth of an inch, mounted on the platform, said router having at least two hand grips and a speed adjustment, and adapted to receive a source of power;
 - an end mill mounted removably on the router; and
- a vacuum fitting, mounted on the platform, wherein an operator adjusts the router vertical adjustment for a desired depth-of-cut, moves the platform continuously along the guide to make a desired cut, and removes debris via the vacuum fitting.
- 25. (Original) The router apparatus of Claim 24, wherein the source of power is electric or pneumatic.